

GLOBE-560XW

2-Way Open-Ceiling Speaker

Globe -560XW is a speaker designed for hanging on very high ceilings (for example, halls of exhibition centers, shopping malls, etc.), where there are no suspended-ceilings or plasterboard structures.

The look is elegant, minimal and the ABS material is of high quality. On rear side, in addition to the Phoenix connections and tap selector, there is a thread for the eyelet screw to which hang on one or more security cables (a steel safety cable with 3mm section and 1m length is supplied).

The high level sound quality is assured thanks to the coaxial transducer with 5.25" (135mm) polypropylene woofer and 1" (25mm) Tweeter with Titanium dome. The integrated line transformer allows the use with 70/100V lines and offers 4 powers + low-impedance, to better adapt to different speaker configurations and amplifier powers. Housing finish is white, but can be painted in any color.







Set up your solutions

PRODUCT DETAILS

Key features

2-Way Coaxial Loudspeaker	
Suitable for very-high open ceilings	
Coaxial Transducer with 5.25" (135mm) Polypropylene Woofer	
1" (25mm) Tweeter with Titanium Dome	
40W RMS Power	
Built-in 70/100V Line Transformer with 4 Power taps + 8ohm	
Extremely Safe Hanging System	
Paintable Housing an Grille	

Specifications

Speaker Type	2-Way Passive, Coaxial	
Line Voltage	70V / 100V	
Line Transformer	Built-in, 4 power taps (+ 8ohm)	
RMS Power	40W @ 8ohm	
Frequency Response (-10dB)	65Hz-20kHz	
Sensitivity (1w/1m)	90dB	
Woofer	5.25" (135mm), Polypropylene cone	
Tweeter	1" (25mm), Titanium dome	
Housing	ABS, paintable	
Mounting	M8 (1 on rear; 1 on side)	
Grille	Perforated steel with acoustic transparent foam inside, paintable	
Color	White	
Product Size (WxDxH)	Ø 195 x 250 mm	
Speaker Weight	2.4 kg	
Packing Size (WxDxH)	230 x 230 x 270 mm	
Packing Weight	3 kg	