

## HYPER BASS SERIES

### Warmly Punching

» **HYPER TOP** full-range speakers were built to provide excellent sound quality and wide frequency response. But when applications demand more bass, **HYPER BASS** subwoofers are the missing link to your HYPER portable sound system. With powerful, warmly punching lows in a lightweight package designed for portability, the **HYPER BASS** series features three bass-reflex active subs delivering up to 1200W on 12" to 18" woofers and birch plywood reinforced enclosures.

- » Integrated active crossover
- » XLR L/R Balanced Line Inputs
- » XLR L/R Balanced Filtered Outputs, XLR L/R Balanced Link Outputs
- » Controls: Sub Level, 80-120Hz crossover switch, 0-180° Phase, Shape switch, Ground Lift On-Off
- » RMS, Overload, Thermal limiter protection
- » Multiplex Birch plywood enclosure with painted black finish
- » 2 lateral recessed handles each side
- » M20 type speaker pole mount to reduce vibrations
- » Predisposition for 4 wheels (not included)



	<b>HYPER BASS12A</b>	<b>HYPER BASS15A</b>	<b>HYPER BASS18A</b>
<b>Speaker Type</b>	Bass-reflex Active Subwoofer	Bass-reflex Active Subwoofer	Bass-reflex Active Subwoofer
<b>Frequency Response(-10 dB)</b>	From 40 Hz to 150 Hz	From 35 Hz to 150 Hz	From 30 Hz to 150 Hz
<b>Max SPL</b>	120 dB	124 dB	126 dB
<b>Crossover Frequency</b>	120 Hz (24dB/Octave)	120 Hz (24dB/Octave)	120 Hz (24dB/Octave)
<b>Woofers</b>	12" (3" v.c.)	15" (4" v.c.)	18" (4" v.c.)
<b>Amplifier</b>			
<b>Amp Class</b>	Class D	Class D	Class D
<b>RMS Power</b>	450 Watt	600 Watt	600 Watt
<b>Peak Power</b>	900 Watt	1200 Watt	1200 Watt
<b>Protection</b>	RMS, Overload, Thermal limiter	RMS, Overload, Thermal limiter	RMS, Overload, Thermal limiter
<b>Input</b>	XLR L + R Balanced Line Inputs	XLR L + R Balanced Line Inputs	XLR L + R Balanced Line Inputs
<b>Output</b>	XLR L + R Balanced Filtered Outputs XLR L + R Balanced Link Outputs	XLR L + R Balanced Filtered Outputs XLR L + R Balanced Link Outputs	XLR L + R Balanced Filtered Outputs XLR L + R Balanced Link Outputs
<b>Controls</b>	Sub Level, 80Hz-120Hz X-over, 0°-180° phase, Shape, Ground Lift	Sub Level, 80Hz-120Hz X-over, 0°-180° phase, Shape, Ground Lift	Sub Level, 80Hz-120Hz X-over, 0°-180° phase, Shape, Ground Lift
<b>Mechanics</b>			
<b>Housing</b>	Multiplex Birch plywood	Multiplex Birch plywood	Multiplex Birch plywood
<b>Finish (Painting type) colour</b>	Painted Black Finish	Painted Black Finish	Painted Black Finish
<b>Handles</b>	1 recessed handles on each side	1 recessed handles on each side	2 recessed handles on each side
<b>Pole Mount</b>	M20	M20	M20
<b>Speaker Dimension (WxHxD)</b>	420 x 520 x 474 mm	460 x 630 x 565 mm	543 x 678 x 620 mm
<b>Net Weight</b>	17 kg	29 kg	37 kg