Verso

The gateway to MyUniverso











Verso is a server gateway designed to allow audio system Monitoring and Control by providing a safe way to connect Powersoft systems to the MyPowersoft cloud, providing streamlined access to the available services, including online storage and remote monitoring.

Verso also helps customers to collect data analytics from their own installations. These data can be used for maintenance/service purposes, and allows more informed system management.

This gateway features a compact 1/2 RU design that is easy to install into a rack, and can be used as a Dynamic Music Distribution system View Host.

With a simple network connection and Powersoft's MyUniverso Cloud, an integrator, tech manager, or technician can quickly and safely monitor and control installed systems remotely.

The Verso gateway supports industry standard, secure data communications, and features dual Gigabit Ethernet ports for isolating AV device traffic from the facility or corporate network.

A redundant power supply helps preventing downtime in mission-critical applications, ensuring continuity of service and data logging even during mains' power outages.

Specifications

Functions		Interfaces		
Provide connectivity for any Powersoft Device to Powersoft Cloud Platform		2x Gigabit LAN	2x Gigabit LAN	
Data gathering for remote monitor and control		1x USB 2.0 for Easy Swap	1x USB 2.0 for Easy Swap	
Up to 200 Amplifier for each Verso				
12 GB onboard storage for data logging & bufferin	g in case of internet connectivity loss	150.		
DMD System Server Capabilities		LEDs		
PoE Support		Power ON status (RGB led)	, ,	
Easy Swap with included USB key		LAN state (RGB Led)		
Manage firmware updates including the ability the push to multiple devices at once		Internet state (RGB Led)		
SNMP Interface and monitoring information				
		Environmental		
Power		Operating temperature range	0°C to +50°C	
Max Consumption	15 W	Operating humidity range	0% to 90% humidity (non condensing)	
		Storage temperature range	-20°C to +85°C	
Connectors				
1 RJ45 for Internet				
1 RJ45 (w PoE) for local network		Construction	4 /2 P.L.	
1xUSB 2.0		Dimensions	1/2 RU 210 x 110 x 40 mm 8.3 x 4.3 x 1.6 inch Rackmount kit included	
UI/Buttons		Weight	750 g (1.65 lb)	
1 Factory Reset button (rear panel)		IP Class	IP 20	

Data subject to change without notice.

