




SUB 12

PASSIVE SUBWOOFER

Subwoofer series takes advantage of tremendous experience in touring, installation and mobile markets. Cabinets are equipped with next-generation transducers with reinforced moving system capable of withstanding tremendous pressure and excursion while keeping distortion in check.

Sub 12 is a compact passive subwoofer for mobile sound reinforcement and small installations. Equipped with 12" long excursion woofer, it is capable of impressive power output with small overall system size.



Main features:

- 450W nominal power
- 12" woofer with 3" voice coil
- Efficient vented box design
- 130,5 dB Max SPL
- M20 distance pole adapter

Frequency Response (-10dB)	45 - 300 Hz
Max SPL ¹	130,5 dB
Sensitivity (1W/1m)	95 dB
LF Driver	12", 3" VC
Impedance	4 / 8 Ohm
Nominal power ²	450 W
Connectors	2x NeutrikSpeakon
Dimensions (W×H×D), mm	390x460x443 mm
Net weight, kg	29 kg
Shipping weight, kg	32 kg
Mounting	M20 distance pole adapter
Enclosure material	Plywood; wear-resistant paint
Grill	Steel grill, acoustically transparent foam

¹ - peak value, calculated according to AES 2 - 2012

² - based on transducer power measured according to AES 2 - 2012